



# ELIT-1050

Digital Signage Player Powered by Intel® Braswell SoC Processor



## Features


- Fanless Design
- Ultra Low Profile Enclosure
- 32GB onboard eMMC memory
- 1 x Full-size Mini-PCIe slot for 3G module or mSATA storage
- Support Dual HDMI
- Support Outside Accessible MicroSD slot
- Support Optional WiFi Connection
- Supports Windows 7/ 8.1/ 10

System	
CPU	Soldered onboard Intel® Celeron® N3060, 1.6GHz
Memory	2 x 204-pin DDR3L SO-DIMM socket, supporting 1600MHz SDRAM up to 8GB (2GB DDR3L SO-DIMM pre-installed)
Chipset	SoC Integrated
Graphics	Intel® HD Graphics 400
ATA	1 x Serial ATA port with 600MB/s HDD transfer rate
LAN Chipset	2 x Realtek 8111HS GbE controllers
Watchdog Timer	1~255 levels reset
I/O	
Serial Port	1 x Micro-B RS232 half-duplex
USB Port	4 x USB 3.0 ports 1 x Micro-B USB 2.0
LAN	2 x RJ-45 ports for GbE
Video Port	2 x HDMI, Max. resolution : 3840 x 2160 @ 30Hz or 2560 x 1600 @ 60Hz
Audio	Realtek ALC255 controller Supports 2/4/5.1/7.1 channel configurations via HDMI 1 x 3.5mm stereo headphone jack
Expansion Bus	1 x Full-size Mini-PCIe slot interconnected with SIM card socket (for 3G module or mSATA) 1 x Half-size Mini-PCIe slot for optional WiFi+Bluetooth module
Environmental	
Operating Temp.	-10 ~ 40 °C (14 ~ 104°F), ambient w/ air flow
Storage Temp.	-20 ~ 60°C (-4 ~ 160°F)
Operating Humidity	0%-85% (non-condensing)
Vibration	3 Grms/5~500Hz/random operation
Shock	Operating 50G (11ms), Non-operating 80G with eMMC


Qualification	
Certification	CE, FCC Class A, UL/CSA
Power Requirement	
Power Input	DC 12~19V input by 2.5mm power jack
Power Consumption	Max. 15W (w/o I/O card)
Storage	
Type	Onboard 32GB eMMC flash memory 1 x mSATA 1 x MicroSD socket, can be outside accessible
Mechanical	
Construction	Aluminum alloy
Mounting	Support VESA-mount/wall-mounting
Weight	0.86Kg (1.89lb)
Dimensions (W x H x D)	140.8 x 27 x 107.5 (5.54" x 1.06" x 4.23")
OS Support	
Windows 7/ 8.1/ 10	
Ordering Information	
ELIT-1050	Digital Signage Player by Intel® Celeron N3060 w/32GB eMMC, 2GB memory and 65W Adapter



# Dimensions



## Standard Accessories

Power Adaptor	19VDC, 3.42A, 60W, 2.5φ JACK, AC/DC Adaptor with US power cord	
---------------	--	---



## Optional Configuration (CTOS\* Kit)

MM-3L-4G	DDR3L-1600 4GB SDRAM	
----------	----------------------	---



32GB SSD	mSATA MLC 32GB	
----------	----------------	---



WiFi-AT2350	Atheros AR9462 WiFi module w/ 20cm & 30cm internal wiring	
-------------	---	---



ANT-D11	1 x Wi-Fi Dual-band 2.4G/5G antenna	
---------	-------------------------------------	---



\*CTOS means Configure-to-Order Service.