

DLS3205

32" TFT LCD,800nits,MaxRGB UHD(3840x2160) SDM Solutions



SDM Ready Display



Key Features

- High Brightness 800 nits
- Sunlight Readable
- LED Backlight
- MaxRGB (NTSC 97%)
- Low Power Consumption
- Support Intel® SDM-S/SDM-L
- Wifi Support

Product Specification

DLS3205	
Description	32" TFT LCD,800nits,MaxRGB UHD(3840x2160) SDM Solutions
Screen size	32"
Display area (mm)	698.4(H) x 392.85(V)
Brightness	800 cd/m2
Resolution	3840x2160
Aspect ratio	16 : 9
Contrast ratio	4500 : 1
Pixel pitch (mm)	0.181(H) x 0.181(V)
Pixel per inch (PPI)	137
Viewing angle	178°(H),178°(V)
Color saturation (NTSC)	97%
Display colors	1.07G
Response time (Typical)	9.5ms
Video interface	SDM-S/SDM-L interface
Input power	AC100~240V
Power consumption	101W (Panel Model Only)
Dimensions (mm)	735.4 x 429.8 x 65.3
Bezel size (U/B/L/R)	16.5/16.5/16.5/16.5 mm
Weight (Net)	12.4kg
Mounting	100x100, 150x150
OSD key	5 Keys (Power Switch, Menu, +, Exit, -)
OSD control	Brightness, Color, Contrast, Auto Turing, H/V Position...etc
Operating temperature	0 °C ~ 50 °C
Storage temperature	
Product a	

SDM From Factor list

Part Number	Description
ASDM-APL5	SDM-L, Intel Apollo Lake CPU,COM/2USB/LAN

Page.33



ASDM-APL6	SDM-S, Intel Apollo Lake CPU.2USB/LAN, LPDDR4-4GB./ eMMC-32GB
-----------	---

Page.34



* Slightly larger than a credit card

Ordering Information

Part Number	Description
DLS3205-INU-M01	32",800nits,3840*2160,MaxRGB,SDM,LID32A, AD9131DHPA, speaker*2,O/B,AC100~240V,V1

Dime

