

Product data sheet

Specifications



Analog high level input module,
Modicon X80, 8 inputs, 0 to 20mA, 4
to 20mA, 10V positive or negative

BMXAMI0800

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Modicon X80
Product or Component Type	Analog input module
Electrical connection	28 ways 1 connector
Isolation between channels	Non isolated
Input level	High level
Analogue input number	8
Analogue input type	Current +/- 20 mA Current 0...20 mA Current 4...20 mA Voltage +/- 10 V Voltage +/- 5 V Voltage 0...10 V Voltage 0...5 V Voltage 1...5 V

Complementary

Analog/digital conversion	16 bits
Analogue input resolution	15 bits + sign
Permitted overload on inputs	+/- 30 mA 0...20 mA +/- 30 mA 4...20 mA +/- 30 V +/- 10 V +/- 30 V +/- 5 V +/- 30 V 0...10 V +/- 30 V 0...5 V +/- 30 V 1...5 V +/- 30 mA +/- 20 mA
Input impedance	10 MOhm in voltage mode 250 Ohm in current mode
Precision of internal conversion resistor	0.1 % - 15 ppm/°C
Type of filter	First order digital filtering
Fast read cycle time	1 ms + 1 ms x number of channels used
Nominal read cycle time	9 ms for 8 channels

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Measurement error	$\leq 0.1\%$ of full scale +/- 10 V 0...60 °C $\leq 0.1\%$ of full scale +/- 5 V 0...60 °C $\leq 0.1\%$ of full scale 0...10 V 0...60 °C $\leq 0.1\%$ of full scale 0...5 V 0...60 °C $\leq 0.1\%$ of full scale 1...5 V 0...60 °C $\leq 0.3\%$ of full scale +/- 20 mA 0...60 °C $\leq 0.3\%$ of full scale 0...20 mA 0...60 °C $\leq 0.3\%$ of full scale 4...20 mA 0...60 °C 0.15% of full scale +/- 20 mA 25 °C 0.15% of full scale 0...20 mA 25 °C 0.15% of full scale 4...20 mA 25 °C 0.075% of full scale +/- 10 V 25 °C 0.075% of full scale 0...10 V 25 °C 0.075% of full scale 0...5 V 25 °C 0.075% of full scale 1...5 V 25 °C 0.075% of full scale +/- 5 V 25 °C
Temperature drift	$30 \text{ ppm}/^\circ\text{C}$ +/- 10 V $30 \text{ ppm}/^\circ\text{C}$ +/- 5 V $30 \text{ ppm}/^\circ\text{C}$ 0...10 V $30 \text{ ppm}/^\circ\text{C}$ 0...5 V $30 \text{ ppm}/^\circ\text{C}$ 1...5 V $50 \text{ ppm}/^\circ\text{C}$ +/- 20 mA $50 \text{ ppm}/^\circ\text{C}$ 0...20 mA $50 \text{ ppm}/^\circ\text{C}$ 4...20 mA
Recalibration	Factory calibrated
Minimum crosstalk attenuation	80 dB
Common mode rejection	100 dB
Digital value format	- 32768 to + 32767 in maximum user scale +/- 10000 by default
Isolation voltage	1400 V DC between channels and ground 1400 V DC between channels and bus
Measurement resolution	0.36 mV +/- 10 V 0.36 mV 0...10 V 0.36 mV 0...5 V 0.36 mV 1...5 V 0.36 mV +/- 5 V $1.4 \text{ }\mu\text{A}$ +/- 20 mA $1.4 \text{ }\mu\text{A}$ 0...20 mA $1.4 \text{ }\mu\text{A}$ 4...20 mA
Maximum conversion value	$\pm 11.4 \text{ V}$ +/- 10 V $\pm 11.4 \text{ V}$ 0...10 V $\pm 11.4 \text{ V}$ 0...5 V $\pm 11.4 \text{ V}$ 1...5 V $0...30 \text{ mA}$ +/- 20 mA $0...30 \text{ mA}$ 0...20 mA $0...30 \text{ mA}$ 4...20 mA $0...30 \text{ mA}$ +/- 5 V
MTBF reliability	1700000 H
Operating altitude	0...6561.68 ft (0...2000 m) 2000...5000 m with derating factor
Status LED	1 LED (Green) RUN 1 LED per channel (Green) channel diagnostic 1 LED (Red) ERR 1 LED (Red) I/O
Net Weight	0.364 lb(US) (0.165 kg)
Power consumption in W	0.90 W 24 V DC typical 1.10 W 24 V DC maximum 0.32 W 3.3 V DC typical 0.48 W 3.3 V DC maximum
Current consumption	150 mA 3.3 V DC 41 mA 24 V DC

Environment

Vibration resistance	3 gn
Shock resistance	30 gn
Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
Ambient Air Temperature for Operation	32...140 °F (0...60 °C)
Relative humidity	5...95 % 131 °F (55 °C) without condensation
IP Degree of Protection	IP20
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility
Product Certifications	CE RCM CSA EAC Merchant Navy UL
Standards	IEC 61010-2-201 IEC 61131-2 UL 61010-2-201 CSA C22.2 No 61010-2-201
Protective treatment	Standard version

Ordering and shipping details

Category	US1PC3418160
Discount Schedule	PC34
GTIN	3595864081557
Returnability	Yes

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.165 in (5.500 cm)
Package 1 Width	4.409 in (11.200 cm)
Package 1 Length	4.724 in (12.000 cm)
Package weight(Lbs)	5.432 oz (154.000 g)
Unit Type of Package 2	S02
Number of Units in Package 2	15
Package 2 Height	5.906 in (15.000 cm)
Package 2 Width	11.811 in (30.000 cm)
Package 2 Length	15.748 in (40.000 cm)
Package 2 Weight	5.829 lb(US) (2.644 kg)
Unit Type of Package 3	P06
Number of Units in Package 3	240
Package 3 Height	29.528 in (75.000 cm)
Package 3 Width	23.622 in (60.000 cm)
Package 3 Length	31.496 in (80.000 cm)
Package 3 Weight	119.050 lb(US) (54.000 kg)

Contractual warranty

Warranty (in months)

18



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Total lifecycle Carbon footprint	83 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile
Carbon footprint of the manufacturing phase [A1 to A3]	20 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	63 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	3377ad7c-3df3-40dc-a26f-b9807ced8c10
REACH Regulation	REACH Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

Lifetime extension

Repair	No
--------	----

Use Again


Repack and remanufacture

Recyclability potential, in %	3
Circularity Profile	End of Life Information
Take-back	No

Dimensions Drawings

Modules Mounted on Racks

Dimensions



(1) With removable terminal block (cage, screw or spring).


(2) With FCN connector.

(3) On AM1 ED rail: 35 mm wide, 15 mm deep. Only possible with BMXXBP0400/0400H/0600/0600H/0800/0800H rack.

Rack references	a in mm	a in in.
BMXXBP0400 and BMXXBP0400H	242.4	09.54
BMXXBP0600 and BMXXBP0600H	307.6	12.11
BMXXBP0800 and BMXXBP0800H	372.8	14.68
BMXXBP1200 and BMXXBP1200H	503.2	19.81

Connections and Schema

Wiring Diagram



VIx + pole input for channel x.

COMx - pole input for channel x, COMx are connected together internally.

IIx current reading resistor + input.

Channel 0 voltage sensor.

Channel 1 2-wire current sensor.

Image of product / Alternate images

Alternative

