


IMB550 NEW

ATX Motherboard with LGA1851 Socket 15th Gen Intel® Core™ Ultra 9/7/5 Processors, Intel® W880, USB 3.2 Gen 2, SATA 3.0, 2.5GbE LAN, DisplayPort++, and HDMI



Features

- LGA1851 socket 15th Gen Intel® Core™ Ultra 9/7/5 processors (Arrow Lake-S)
- Four 288-pin DDR5-4400 ECC/non-ECC unbuffered Long-DIMM, up to 192GB
- Supports DisplayPort++ and HDMI
- Supports 2 x M.2 Key M 2280
- Supports 2 PCIe x16 slots with PCIe Gen 5 for GPU cards
- Supports IPMI 2.0
- Optimized CPU socket layout design for airflow of rackmount system

Specifications

Core System

CPU	LGA1851 socket 15th Gen Intel® Core™ Ultra 9/7/5 processors, up to 125W (Arrow Lake-S)
System Memory	4 x 288-pin DDR5-4400 ECC/non-ECC un-buffered Long-DIMM, up to 192GB (ECC memory available only for Intel® W880)
Chipset	Intel® W880
BIOS	AMI BIOS
SSD	2 x M.2 key M 2280 in support of PCIe x4 via CPU with RAID 0/1
Watchdog Timer	255 levels, 1 to 255 sec.
Expansion Interface	2 x PCIe Gen 5 x16 slots (signal: PCIe x16 + PCIe x0 or PCIe x8 + PCIe x8) 5 x PCIe x4 slot open ended 3 x PCIe x4 signal, slot 3 & 6 PCIe x2 signal (signal by PCH)
Battery	Lithium 3 V/ 220 mAh

Specifications

Display

Chipset	Intel® X ^e LPG Graphics
Memory Size	Share system memory
Display Interface	1 x HDMI 1.4b, up to 4096 x 2160 @ 24Hz 1 x Displayport++ (DP 1.2), up to 4096 x 2304 @ 60Hz

I/O

SATA	4 x SATA-600 with RAID 0/1/5/10
Hardware Monitoring	Detect CPU/system temperature, voltage, and supports smart fan control
Ethernet	1 x 10/100/1000 Mbps with Intel® I219-LM supporting Wake-on-LAN, PXE Boot ROM, and Intel® AMT with Intel vPro® 2 x 10/100/1000/2500 Mbps Ethernet with Intel® I226-V supporting Wake-on-LAN, and PXE Boot ROM 1 x 10/100/1000Mbps IPMI LNA Intel® I210-AT shared with AST2600, supports Wake-on-LAN, and PXE Boot ROM (option)
Audio	HD Codec audio as MIC-in/Line-in/Line-out
USB	4 x USB 3.2 Gen 2x1 (10G) & 4 x USB 3.2 Gen 1x1 (5G) (rear I/O) 2 x Dual USB 3.2 Gen 1x1 (5G) (internal, box header) 1 x USB 2.0 (internal, 180D Type-A)
Serial	2 x RS-232 (internal box header) 2 x RS-232/422/485 (internal box header)
PS/2 Port	1 x PS/2 keyboard (rear I/O) 1 x PS/2 mouse (rear I/O)
TPM	TPM 2.0
SMBus	Yes
Digital I/O	8-channel programmable
Remote Management	IPMI 2.0 supported by OpenBMC

Mechanical and Environmental

Dimensions	305 x 244 mm
Board Thickness	1.6 mm
Operating Temperature	0°C to +60°C (+32°F to +140°F)
Relative Humidity	10% to 95% relative humidity, non-condensing

Ordering Information

Standard

IMB550-ARL-W880 SP (P/N: TBC)	ATX motherboard with LGA1851 socket 15th Gen Intel® Core™ Ultra 9/7/5 processors, Intel® W880, USB 3.2 Gen 2, SATA 3.0, 2.5GbE LAN, DisplayPort++ & HDMI, and single pack
IMB550-ARL-W880 BP (P/N: TBC)	ATX motherboard with LGA1851 socket 15th Gen Intel® Core™ Ultra 9/7/5 processors, Intel® W880, USB 3.2 Gen 2, SATA 3.0, 2.5GbE LAN, DisplayPort++ & HDMI, and bulk pack

Optional

5948C122800E	2 x USB 3.2 Gen1 cable with bracket, L=400 mm
594G5208000E	SATA 3.0 signal cable, L=500 mm with locking latch
594G5208010E	SATA 3.0 signal cable, L=500 mm without locking latch
59380402010E	1 x COM port cable with bracket, P=2.54 mm, L=300 mm
59380703000E	2 x COM port cable with bracket, P=2.54 mm, L=300 mm
713000000500	1U CPU cooler with smart fan
711000002500	CPU cooler for 2U, 4U, and wall mount chassis with smart fan

*Please refer to the user manual for the complete list of supported CPUs.